



Hoomline Brillant 55 Click

PROPERTIES	STANDARD	UNIT	TEST RESULT
Plank size	EN 427	cm	228*1230*5.5mm
Thickness	EN 428	mm	5.5 mm
Wearlayer	EN 429	mm	0,55 mm
Surface treatment			BP
Bevel			4-side bevel
Click			unilin 2G
Weight per sqm	EN 430	gr/m2	8200
Pieces per box (plank)		piece	8
Sqm per box (plank)		m2	2,24
Boxes per pallet (plank)		box	56
Sqm per pallet (plank)		m2	125,64
Classification	EN 685	class	34
Fire classification	EN 13501-1	class	Bf1-S1
Slipresistance	DIN 51130	class	R9
	EN 13893	class	DS
Weargroup	EN 660-1		T
Residual indentation	EN 433		0.05 mm
Thermal conductivity	EN 12667:2001		0.076 W/(m·K)
Thermal resistance	EN 12667:2001		0.039(m2.k)/W
Electrostatic properties	EN 1815		<2.0 KV
Castor chair	EN 425		yes type W EN12529
Dimensional stability	EN 434		≤0.01%
Light fastness	ISO 105-BO2	degree	level ≥6 method A
Determination of impact sound	E 492-09		IIC=63
Sound reduction	ISO 717-2		10 dB
Chemical resistance	EN 423		yes
Floor heating system		degree	suitable max.27°C
CE marking	EN 14041		EN 14041:2004+AC:2005+AC:2006
Guarantee			residential 25 years - commercial 10 years

Deutsches
Institut
für
Bautechnik

